FOX PVAc HIJAU

TYPE : Water based adhesive

APPLICATION : - General purpose adhesive for wood, packaging, and construction (for wall putty)
- Also for gluing metalizing particles to prada cloth

TECHNICAL SPECIFICATION :

* Base	:	Polvinyl acetate homopolymer
* Appearance	:	White emulsion
* Viscosity	:	90,000 – 140,000 cPs at 28 °C, Brookfield RVT / sp. 7/20 rpm
* Solid content	:	31 ± 2 %
* pH	:	4 – 6
* Density	:	1.02 ± 0.05 g/mL at 28 °C
* Glue film	:	Tough, translucent
* Diluting agent	:	Water, not more than 5 %

DIRECTION FOR USE

* For brush or glue spreader application

SHELF LIFE : 12 months, in tightly closed container and stored in a cool and dry place

PACKING : - 400 g in PP plastic bag (48 bags / carton)
- 400 g in PP plastic bag (430 bags / metal drum)
- 700 g in PP plastic bag (24 bags / carton)
- 700 g in PP plastic bag (240 bags / metal drum)
- 5 kg in carton

NOTE :
All information, whether written or verbal, regarding our products, their applications and uses, is given in good faith and based upon tests made by us, results of our research work and practical experience. Whilst we guarantee the constant quality of our products, we cannot be responsible for the results obtained in their use since the conditions of use and working methods are beyond our control. We disclaim third party's liability for the results obtained using our products, and recommend that the test should be made to determine the suitability of a particular product for a specific purpose before production will commence. Our technical data sheets are constantly revised to represent the latest state of technology and our customer's requirements.

WB/06/V/22